

PRODUCT:

Selective Laser Sintering (SLS) - PA12

Nylon PA12, a high-performance polyamide powder used in Selective Laser Sintering technology, offers exceptional versatility and reliability for a wide range of applications. Known for its high precision, low cost, and excellent mechanical properties, this material is ideal for rapid prototyping and finished consumer products alike. Its low moisture absorption ensures excellent chemical resistance, while its biocompatibility makes it suitable for medical applications, including prosthetics.



Highly durable, Nylon PA12 provides outstanding abrasion resistance, UV stability for outdoor use, and the ability to create complex movable connections like gears and hinges. This adaptability makes it a top choice for innovative and demanding manufacturing needs.

PART PROPERTIES	VALUE
Average grain Size (µm)	58-60
Bulk Density (g/L)	435 - 470
Tensile Modulus (N/mm ²)	1700 (+/- 150)
Tensile Strength (N/mm ²)	42 - 50
Elongation at break - XY (%)	11
Elongation at break - Z (%)	3 - 9
HDT (A) - (DIN EN ISO 75) - 1.80 MPa	85° C
HDT (B) - (DIN EN ISO 75) - 0.45 MPa	170° C

The information provided in this data sheet is based on appropriate testing, details of which can be made available upon request. It reflects our knowledge and understanding at the time of publication. However, it is offered without any contractual obligations and does not guarantee or warrant specific properties, processes, or applications in individual cases, whether expressed or implied. This data is subject to change without prior notice as part of our continuous development and improvement efforts. Additionally, the content of this material data sheet may be protected by copyright laws. The cited results are drawn from Sculpteo test data, supplier materials, and may also include values from other material-specific sources.

Revision date: June 2026